



450

STEINER



37
EFI



IT'S NOT A
TRACTOR,
IT'S A







FOUR SEASONS. ONE TRACTOR.

It doesn't matter what season it is. What the conditions are. Or what's in front of you. Steiner is built to get it done. With a reputation for uncompromising versatility, Steiner gives you performance along with a range of four-season attachments that let you tackle tough jobs—all year long. Whether you're maintaining a farm, commercial or residential property, golf courses, municipal grounds or sports turf, you can rely on Steiner. Because they're **BUILT FOR DOING.**

STEINER®450

GO ANYWHERE. DO ANYTHING.

SUPERIOR STABILITY. POWERFUL PERFORMANCE. FOUR-SEASON VERSATILITY.

Don't call it a tractor. Call it a Steiner. The original, articulating, oscillating, go-anywhere, do-anything, get-it-done machine.

- Effortlessly navigate rolling and rugged terrain and slopes—stable up to 30 degrees when equipped with dual wheels—with its wide-stance oscillating frame, four-wheel drive and adjustable-on-the-fly hydraulic weight transfer.
- Power through tough tasks quicker and more efficiently with three configurable, commercial engine options.
- 14 attachments means 24/7/365 versatility for any job—in any season.

ATTACHMENTS

- Rough Cut Mower
- Flex Deck Finish Cut Mower
- Side-Discharge Rotary Mower
- Core Aerator
- Slip Scoop
- Stump Cutter
- Turbine Blower
- Lawn Sweeper
- Professional Snow Blower
- Rotary Sweeper
- Power Angle Blade
- Adjustable V-Blade

TRACTOR ACCESSORIES

- Deluxe Cab
- Dual Wheel Kits
- Hand Control
- Weight Kit
- Front Fenders
- Foot Pegs
- Suspension Seat
- Front Power Outlet
- Rear Power Outlet
- Slope Meter
- ROPS Canopy
- 3-Point Hitch
- Front & Rear Aux. Hydraulics
- Rear Quick Hitch
- 3" Wheel Spacer
- Front weight bar
- Low Seat Plate
- Engine overhead Protection
- Back up Beeper





 **30° SLOPES**

450 TRACTOR SPECIFICATIONS

<p>DIMENSIONS</p>	<p>Overall width: 44.5", 50.5" with 3" wheel extensions, 66.5" with dual wheels Overall length: 80.5" with ROPS up Overall height: 73.5" with ROPS up; 55" with ROPS folded Wheelbase: 43.5" Minimum ground clearance: 4.75" Frame oscillation: 9" Turning radius: 43.5" Weight: Kubota® D902: 1665 lb Kubota® WG972: 1660 lb Vanguard® M61 EFI: 1575 lb</p>
<p>ENGINES</p>	<p>Kubota® D902 diesel, liquid-cooled, 898 cc, 24.8 hp Kubota® WG972 gas, liquid-cooled, 962 cc, 32.5 hp Vanguard® M61 EFI gas, air-cooled, 993 cc, 37 hp</p>
<p>HYDRAULICS</p>	<p>Implement pump: Turolla Group 2 Series fixed-displacement, stacked configuration Flow capacity: 6 gpm @ 3600 RPM Lift, steering, auxiliary pressure: 1750 PSI Hydraulic oil capacity: 5.25 US gallons</p>
<p>TRANSMISSION</p>	<p>Hydrostatic drive pump: Eaton® Model 70160, variable-displacement piston pump Transaxles: (2) Peerless® 2600 dual-range Speeds: High range: 9.5 MPH forward, 7.0 MPH reverse Low range: 6.0 MPH forward, 4.5 MPH reverse Steering: Hydraulic power steering Brakes: Single, mechanical disc</p>
<p>ATTACHMENT DRIVE</p>	<p>Front PTO clutch: Warner® CMS 250 Series electric clutch/brake Hydraulic outlets: Quick couplers-front</p>
<p>SLOPE RATINGS</p>	<p>Continuous: 20° max. Intermittent (10 minutes or less): 30° max With cab: 10° (18%)</p>
<p>FUEL SYSTEM</p>	<p>Tank capacity: 7 US gallons</p>
<p>TIRES</p>	<p>Field Trac 22x12-10 Bar 22x12-10 Turf 22x11-10</p>
<p>HITCH</p>	<p>Front: Steiner® Quick-Hitch system Back: Standard 2" receiver hitch, with optional category 1 three-point hitch</p>
<p>HIGH-BACK BUCKET SEAT</p>	<p>Deluxe, high-back bucket seat with armrests and rear storage pouch Adjustment: 6" fore and aft</p>
<p>ADDITIONAL FEATURES</p>	<p>Lighting: Dual LED headlights and tail lights Storage compartment: Standard Cup holder: Standard Front and rear skid plates: Standard PTO tension adjustment: Manual Rollover Protective Structure (ROPS): Standard, folds down 12 volt outlet: Standard, 15 amp Optional front fender kit Optional hand-lever speed control</p>



FLAIL MOWER

NEW THIS YEAR



THE PERFECT CUT AND FINISH

Effectively cut through tall, heavy grass and brush up to 3/4" diameter. Easily transition from rough cutting to finish cutting by utilizing the optional scoop knives.

MODEL 7450787

- Overall Width: 78.7"
- Overall Length: 41.6"
- Overall Height: 16.1"
- Max. Working Width: 72"
- Number of Knife Blades
 - Y Knives: 72
 - Scoop Knives: 36
- Height of Cut increments: 1/2"
- Striping Roller: Yes
- Tie Down Points: 4
- Weight: 490 lbs.
- Drum RPM: 2600
- Versatility: Quickly change the cutting knives to go from rough cutting to finish cutting in a matter of minutes
- Available options: Scoop Knives for finish cutting (Part Number: 7462681)

GO ANYWHERE. DO ANYTHING.

STEINER

FLEX DECK MOWER



TACKLE UNEVEN TURF

Four independent, 21-inch decks with powerful torque allow the Flex Deck Mower to deliver a high quality, professional cut on uneven, sloped terrain—pushing productivity to all-new heights and angles.

MODEL 75-71305B

- Overall width: 82" (70" with trim-side deck raised, 94" with chute down)
- Overall cutting width: 80"
- Decks: 4 hinged, 20° articulation
- Trim-side deck: 20" offset, hydraulic lift
- Cutting height: 1 1/2" to 5"
- Spindles: Cast-iron, sealed ball bearings
- Blades: 4 high-lift blades, 21"
- Wheels: 5 front, 2 rear, 9" x 3.5" each, no flat, semi-pneumatic
- Discharge: Side
- Weight: 760 lb
- Available options: Mulching baffle kit (part #: 75-71313)





ROUGH CUT MOWER

MOW DOWN TALL GRASS AND SAPLINGS

Delivering a 72-inch width of cut that overpowers the roughest, toughest brush (up to a diameter of 1.5 inches), the Rough Cut Mower lets nothing stand in your way.

MODEL 7436122

- Overall width: 73" (deck 76" with skids)
- Cutting width: 72"
- Cutting height: 3 3/4" to 6"
- Drive: Shaft to PTO belt
- Spindles: Cast-iron, sealed ball bearings
- Blades: 3 blades, 24"
- Discharge: Rear
- Skid shoes: 2
- Weight: 515 lb
- Available options: Counter-rotating blade kit (part #: 75-71302)

GO ANYWHERE. DO ANYTHING.



LAWN SWEEPER



FLAWLESS CLEAN UP

With a tow-behind, durable design and versatile sweeping options, the Lawn Sweeper features an enclosed 24-cubic-foot chamber that scoops up wet and dry leaves, lawn clippings and debris, then tightly packs them to maximize capacity.

MODEL LS340

- Overall width: 62"
- Overall height: 52"
- Overall length: 82"
- Width of pickup: 40"
- Brush: 3-paddle, staggered
- Depth wheels: Semi-pneumatic
- Hitch: Right, left or center pull
- Carrying capacity: 24 cu ft
- Weight: 530 lb

SIDE-DISCHARGE ROTARY MOWER



DEPENDABLE, SIMPLE AND A PERFECT FINISH

Featuring a full-floating deck with three blades, the Side-Discharge Rotary Mower cuts with maximum precision and consistent clipping distribution—with an easy-to-use, fully adjustable deck that flips up for hassle-free servicing.

MODEL MD460

- Overall width with discharge chute: 74"
- Cutting width: 59 3/8"
- Cutting height: 1" to 4 1/2"
- Spindle drive: Single "V" belt
- Spindles: Tapered roller assemblies

- Blades: 3 blades, 20 1/2"
- Discharge: Side
- Wheels: 10 x 3.5 semi-pneumatic
- Weight: 360 lb
- Drive: Shaft to PTO belt

MODEL MD472

- Overall width with discharge chute: 86"
- Cutting width: 72"
- Cutting height: 1" to 4"
- Spindle drive: Single "V" belt
- Spindles: Tapered roller assemblies

- Blades: 3 blades, 24 3/4"
- Discharge: Side
- Wheels: 10 x 3.5 semi-pneumatic
- Weight: 470 lb
- Drive: Shaft to PTO belt

GO ANYWHERE. DO ANYTHING.



STUMP CUTTER



ELIMINATE UNSIGHTLY STUMPS

Adjustable both laterally and vertically, equipped with a 16-inch-diameter, carbide-teeth cutting wheel and powered by a right-angle gearbox for lasting performance, the Stump Cutter chops through stubborn stumps and rigid roots.

MODEL SC101

- Overall width: 34 1/2"
- Overall height: 18"
- Overall length: 37"
- Cutterhead:
24 carbide teeth
- Cutterhead diameter: 16"
- Cutterhead width: 3 1/4"
- Cutterhead speed: 1600 RPM
- Cutting depth below ground level: 5"
- Maximum recommended cutting height above ground level: 5"
- Weight: 250 lb



CORE AERATOR

AERATE EFFICIENTLY AND EFFECTIVELY

The Core Aerator's 42-inch aeration width and independent 3/4-inch core tine assemblies allow you to follow contours and pull quality, precise cores up to 3 1/2 inches deep in the most challenging turf—helping reduce compaction and improve overall turf health.

MODEL AR240

- Overall width: 45 1/2"
- Working width: 40 1/4"
- Overall height: 28 1/2"
- Overall length: 30"
- Main shaft bearings: Greasable, 1 1/2"
- Tines: 6 per wheel, 3/4" core tines
- Aerating wheels: 7 steel with bushings/pressurized lubrication fitting
- Aerating width: 42" actual; 48" effective
- Aerating depth: Up to 3 1/2"
- Aerating pattern: 6 1/2" x 7" (3.6 holes/sq ft)
- Weight: 390 lb with 4 weights

GO ANYWHERE. DO ANYTHING.

STEINER

TURBINE POWER BLOWER



QUIET AND POWERFUL

The Turbine Power Blower easily blows away leaves and debris and boasts a powerful—yet quiet—axial-flow turbine design that produces wind speeds up to 114 mph and from a hydraulically controlled, 360-degree rotating nozzle.

MODEL PB200

- Overall width: 27"
- Overall height: 33"
- Overall length: 67"
- Airflow: 8000 cfm
- Wind speed: 114 MPH
- Wind speed (deflected to front): 78 MPH
- Sound level (while seated in operator seat): 91 dBA
- Weight: 235 lb
- Weight on caster: 195 lb

SLIP SCOOP



LIFT. HAUL. DUMP.

With a compact design and simple hydraulic operation that deliver the power and versatility to move heavy loads, the Slip Scoop effortlessly tackles small excavation, landscaping and turf projects.

MODEL SS248

- Overall width: 52"
- Overall height: 15.25"
- Overall length: 33"
- Width of bucket: 48"
- Bucket capacity: 4.5 cu. ft.
- Dumping: Hydraulic
- Scarifier teeth: 6 - 1" wide (optional)
- Weight: 170 lb
- Available options: Scarifier wear edge (part #: 78-043)

GO ANYWHERE. DO ANYTHING.



POWER ANGLE BLADE



THE DO-IT-ALL BLADE

The Power Angle Blade charges through dirt, gravel and snow with a ruggedly built, hydraulic blade and a reversible cutting edge for long-lasting performance during any season. Equipped with trip protection to reduce hang-ups when plowing and a locking pin to prevent folding back when dozing.

MODEL BD260

- Blade width: 60"
- 30° angled width: 48"
- Overall height: 19"
- Overall length: 32"
- Blade height from cutting edge: 19"
- Hydraulic angling: 30° left and right
- Skid shoe: Adjustable
- Forward tilt: Spring-loaded
- Reversible cutting edge: 3" hardened
- Weight: 195 lb
- Available options:
 - Gauge wheel (part #: 75-70510)
 - Poly blade edge (part #: 970421)
 - Heavy duty wear edge (part #: 78-038)
 - Scarifier wear edge (part #: 78-040)

ROTARY SWEEPER



A FOUR-SEASON WORKHORSE

Delivering on-demand power and control, the Rotary Sweeper brushes away leaves, debris and light snow on pathways, parking lots and drives in one clean sweep.

MODEL RS350

- Overall width: 61"
- Overall height: 18"
- Overall length: 44"
- Brush width: 54"
- Brush diameter: 15"
- Working width: 54"
- Hydraulic angling (left & right): 30°
- Speed of brush: 300 RPM
- Engine speed: 3200 RPM
- Gearbox: Beveled gears
- Weight: 170 lb
- Brush rotation: Forward

MODEL RS454

- Overall width: 62"
- Overall height: 29"
- Overall length: 44"
- Brush width: 54"
- Brush diameter: 24"
- Working width: 54"
- Hydraulic angling (left & right): 30°
- Speed of brush: 265 RPM
- Drive: Variable-speed, hydraulic
- Weight: 475 lb
- Brush rotation: Forward and reverse

GO ANYWHERE. DO ANYTHING.



PROFESSIONAL SNOW BLOWER



ALL-WINTER-LONG RELIABILITY

Cutting a wide, 48-inch path (52-inches with optional wing extensions) with a serrated auger and four-blade blower, the Professional Snow Blower powers through winter's heaviest and deepest snowfalls.

MODEL SB648

- Overall width: 48"
- Overall length: 44"
- Opening size: 27" high x 48" wide
- Serrated auger: 16" diameter, open center
- Blower: 18" diameter, 4 blades, 7" depth
- Width of cut: 48"
*52" with optional wing extensions
- Auger speed: 140 RPM
- Blower speed: 700 RPM
- Chute: Approximately 7" diameter, 223° rotation
- Height of cut: Adjustable skid shoes, 0" to 3/4"
- Weight: 450 lb
- Available options:
 - Electric chute deflector (part #: 75-71234A)
 - Drift cutters (part #: 75-71235)
 - Extension wings (part #: 75-7236)



ADJUSTABLE V-BLADE

MULTIPOSITION VERSATILITY

With an electro-hydraulic, independent blade-wing, the Adjustable V-Blade easily converts from a v-blade for splitting paths through heavy snow to an inverted scoop or straight blade for moving large amounts of material.

MODEL BD358

- Overall width: 69 1/4"
- Cutting width: straight/angled: 58"; scoop: 49"; V-blade: 53"
- Overall height: 21"
- Overall length: 31"
- Blade height from cutting edge: 21"
- Angling: 30° left and right, front and back
- Skid shoes: Adjustable
- Forward tilt: Spring-loaded
- Cutting edge: 2-position; 3/8" x 4" hardened
- Weight: 248 lb

GO ANYWHERE. DO ANYTHING.

STEINER

Your safety is important to us.
Before operating any power equipment, consult your operator's manual for safe operating and maintenance procedures.

All Steiner® products are covered by a 2-year limited warranty.
Please see your local dealer for full warranty details or consult the product manual.



Steiner | One Bobcat Lane | Johnson Creek, WI 53038

For more information about Steiner products, visit your Steiner dealer today.
For the location of the dealer nearest you, call 1-866-469-1242 or visit steinerturf.com.

STEINERTURF.COM