

IT'S NOT A
TRACTOR, IT'S A
STEINER



450

GO WHERE OTHERS WON'T.
DO WHAT OTHERS CAN'T.

450 TRACTOR SPECIFICATIONS



Dimensions:

Overall Width: 44.5", 50.5" with optional wheel extensions,
66.5" with dual wheels

Overall Length: 80.5" with ROPS up

Overall Height: 73.5" with ROPS up, 55" with ROPS folded

Wheelbase (front to rear axle): 43.5"

Minimum Ground Clearance: 4.75"

Frame Oscillation: 9"

Frame Articulation: 36 degrees, 43.5" turning radius with inner steering cylinder rear mount location, 56.0" turning radius with outer steering cylinder rear mount location

Hydraulics:

Implement Pump: Turola Group 2 Series, Fixed Displacement Gear Pump,
Stacked Configuration

Flow Capacity (gpm): 6 gpm @ 3600 RPM

Lift, Steering, Auxiliary Pressure: 1750 PSI

Hydraulic Oil Capacity: 5.25 US Gallons

Transmission:

Drive Train: Eaton® model 70160, Variable Displacement Piston Pump

Transaxles: (2) Peerless® 2600 Dual Range

Speeds: 0-9.5 MPH Forward, 7.0 MPH Reverse-High;

0-6 MPH Forward, 4.5 MPH Reverse-Low

Steering: Hydraulic Power Steering

Brakes: Dual Disc and Front and Rear Axles

Attachment Drive:

Front PTO Clutch: Warner® CMS 250 Series

Electric Clutch/Brake

Hydraulic Outlets: Quick Couplers-

Front Auxiliary

Fuel System:

7 US Gallon Tank Capacity

Wheels:

Field Trac (All Terrain) 22x12-10

Mag Off Road (Bar) 22x12-10

Lightfoot (Turf) 22x11-10

Hitch:

Front: Steiner® Quick-Hitch™, with standard front release control

Back: Standard 2" receiver hitch, with optional category 1 three-point hitch

High-Back Bucket Seat with Rear Storage Pouch:

Armrests: Standard

Suspension: Radial Bearing Suspension, optional Mechanical Suspension

Adjustment: 6" Fore and Aft

Additional Features:

Lighting: Dual LED Headlights and Taillights

Storage Compartment: Standard

Cup Holder: Standard

PTO Tension Adjustment: Manual

12 Volt Outlet: Standard – 15 Amp

► MODEL SPECIFICATIONS

Model #	75-75025	75-75032	75-75037
Engine	Kubota® D902	Kubota® WG972	Vanguard™ M61 EFI
Max Operating Speed	3600 rpm	3600 rpm	3600 rpm
Fuel Type	Diesel	Gasoline	Gasoline
Horsepower (Gross)	25 hp	32.5 hp	37 hp
Displacement	898 cc	962 cc	993 cc
Cylinders	3	3	2
Cooling	Liquid	Liquid	Air
Fuel Capacity	7 gal	7 gal	7 gal
Charging	40 Amp	40 Amp	50 Amp
Battery	630 CCA	450 CCA	450 CCA
Slope Rating, Continuous	20° Max	20° Max	20° Max
Slope Rating, Intermittent (10 minutes or less)	30° Max	30° Max	30° Max
Weight (with Field Trac tires and fuel)	1665 lb	1660 lb	1575 lb

Steiner® uses commercial-strength engine options for longevity and ease of service. All engines are warranted by their respective manufacturer and your local dealer. The power engine ratings are provided by the engine manufacturer. Actual power output is dependent on many factors including engine rpm, air density and engine condition.



All Steiner products are made with pride in the U.S.A. and are warranted commercially for 2 years. Please see your local dealer for full warranty details also found in the product manual. Your safety is important to us. Before operating any turf maintenance equipment, consult your operator's manual for safe operating and maintenance procedures.

For more information about Steiner® products, visit your Steiner® dealer today.
For the location of the dealer nearest you, call 1-866-469-1242 or 1-920-699-2000.
Visit us on the Web at www.steinerturf.com



Steiner® is a registered trademark of Schiller Grounds Care, Inc.

©2018 Schiller Grounds Care, Inc. Company. All rights reserved. Steiner | One BOB-CAT Lane | Johnson Creek, WI 53038