



235 Tractor



Compact with plenty of power and versatility, the Steiner 235 model tractor is game for any task. With a low center of gravity, the 235 tractor is stable and comfortable. Equip it with 16 optional attachments and go to work.

- Powerful Hydrostatic Front Wheel Drive
- Easy Foot Controlled Forward and Reverse
- Productive Differential Lock Links Both Drive Wheels for Even Traction
- Maneuverable Rear Wheel Power Steering
- Tight 14-inch Front Wheel Turning Radius
- Steady and Stable Traction-Max™ Weight Transfer System
- Simple Two-Point Quick-Hitch™ Attachment System Requires No Tools
- Handy Auxiliary Hydraulics for Optional Attachments



Slip Scoop



Snow Blower



Tiller

MOW IT ▸ BLOW IT ▸ TRENCH IT ▸ HAUL IT ▸ DRILL IT ▸ TILL IT **DO IT.**

DO IT.

Steiner 235 Tractor Features

Weight Transfer	Trademarked Traction-Max™ Hydraulic Weight Transfer System. Uses the 430 model tractor control valve to charge weight transfer accumulator, with a needle valve added to eliminate pressure leak.
Drive	Robust drive shaft with shock-absorbing element.
Controls	Hi-Low Range selector lever with safety lock on console for easy access.
Power Take-Off	PTO Slider Bracket with round shaft.
Clutch	Large capacity Warner 175 ft lb clutch with large support bearing, with rotation stop.
Tires	6-ply Off-Road 350 Mag front tires.

Steiner 235 Tractor Specifications

(235D Factory Model number 75-70282; 235G Factory Model number 75-20283)

Engine: 235D – Kubota Diesel D1105, 3 Cylinder, 24.8 Gross Horsepower Liquid-cooled, 1123 cc Displacement, 3600 RPM

235G – Briggs and Stratton Vanguard, V-Twin Cylinder, 35 Gross Horsepower Air-cooled, 992 cc Displacement, 3600 RPM

Charging System: 40 AMP

Battery / Ignition: 235D – 40 AMP Charging System / 12 Volt Battery 620 CCA at zero degrees F / Key Switch Ignition

235G – 50 / 20 AMP Charging System / 12 Volt Battery 525 CCA at zero degrees F / Key Switch Ignition

Transmission: Sundstrand Series 15 U-type hydrostatic piston pump motor.

Transaxle: 2-speed Peerless 2600 Series with differential lock.

Traction Boost: Traction-Max™ adjustable weight transfer with pressure gauge indicator.

Power Take-Off: Warner 175 ft lb electric clutch.

Speeds:

Forward/Reverse 0-10 MPH (0-16.09 kmh) (high range)
0-5 MPH (0-8.05 kmh) (low range)

Steering: Hydraulic power steering.

Brakes: Individual wheel drum turning brakes.

Lighting: Dual headlamps. Dual tail lights.

Seat: Extra large deluxe contoured seat standard.

Fuel Tank Capacity: 6 US gallons.

Fuel Pump: Electric

Tires, Drive: 24 x 11-2, 350 Mag, 6-ply

Tires, Rear: 18 x 8.50-8, Turf Glide ribbed 4-ply

Attachments: No tool, Quick-Hitch™ Mounting System.

Rollover Protective Structure: Optional

Warranty: Two years commercial use. See warranty statement for more details.

Instrumentation: Analog: Tachometer and hour meter. Coolant temperature gauge. Fuel gauge. Charging system indicator light.

Indicator Lights: Engine oil pressure. Charging system. Glow plug. PTO.

Overall Width: 56 in (147.32 cm)

Overall Length: 82 in (208.28 cm)

Overall Height: 45 in (114.13 cm)

Wheelbase: 50 in (127.0 cm)

Inside Turning Radius: 14 in (35.50 cm) (Measured at the front wheel)

Weight: 1420 lbs (644.10 kg)

Specifications, while correct at time of printing, may change without notice.

16 Available Steiner Attachments

RC646 Rough Cut Mower | **MX460** 60-inch Rotary Mower | **MD472** 72-inch Mower Deck

MD460 60-inch Mower Deck | **SB348** Snow Thrower | **MH100** Machinery Hitch

SS248 48-inch Slip Scoop | **RS454** Hydro Rotary Sweeper | **BD272** 72-inch Dozer Blade

BD260 60-inch Dozer Blade | **TL348** 48-inch Rotary Tiller | **AR240** Core Aerator

PB200 Turbine Blower | **PB100** Power Blower | **RS350** 54-inch Rotary Sweeper | **BD358** V-Blade



All Steiner products are made with pride in the U.S.A. and are warranted commercially for 2 years. Please see your local dealer for full warranty details also found in the product manual. Your safety is important to us. Before operating any turf maintenance equipment, consult your operator's manual for safe operating and maintenance procedures.

For more information about Steiner products, visit your Steiner dealer today.
For the location of the dealer nearest you, call 1-866-469-1242 or
1-920-699-2000. Visit us on the Web at www.steinerturf.com.